



NANO-GEL TECHNOLOGY GEL

MOTORCYCLE BATTERIES

power on command

- ⚡ Extreme starting performance, even in cold weather
- ⚡ Extreme high capacity to support accessories
- ⚡ Extreme low self-discharge

Thanks to the electrolyte thickened to Nano-Gel, this battery has lower self-discharge. Furthermore, the construction of this battery provides more power than equivalent DRY/AGM or SLA batteries. This makes it highly suitable for motorcycles with higher power consumption, such as those with fog lights, heated grips, navigation, USB, and other additional electronic accessories. This battery is already factory activated (filled and charged) and therefore ready to use! It is 100% maintenance free, completely sealed, spill-proof and leak-proof which makes this battery ultra-safe.

MODELS & SPECIFICATIONS

Article Number	Nominal Voltage (V)	Capacity Ah (10hr)	CCA	Length (mm)	Width (mm)	Height (mm)	Layout	Terminal
MG LB4-3	12	4	60	120	71	91		
MG LTX4-3	12	4	60	113	69	85		
MG LB5-3	12	5	80	120	60	128		
MG LTX5-3	12	5	90	113	69	105		
MG LT7B-4	12	6	125	150	65	92		
MG LTZ7-S	12	6	130	113	69	105		
MG LTX7-3	12	7	120	113	69	130		
MG LTX7A-4	12	7	125	150	86	94		
MG LT9B-4	12	8	135	150	69	105		
MG LTZ10-S	12	8,6	190	150	86	94		
MG LTX9A-4	12	9	145	135	75	139		
MG LTX9-4	12	9	145	150	86	105		
MG LT12B-4	12	10	150	150	69	130		
MG LB10-3	12	11	150	134	88	145		
MG LTZ12-S	12	11	210	150	86	110		
MG LTZ14-S	12	11,2	245	150	86	111		
MG LB12A-4	12	12	170	134	80	161		
MG LB12A-3	12	12	170	134	80	161		
MG LT14B-4	12	12	180	150	69	145		
MG LTX12-4	12	12	215	150	86	130		
MG LTX14AH-3	12	14	240	134	88	166		
MG LTX15-3	12	14	240	175	87	130		
MG LTX14-4	12	14	240	150	86	145		
MG LB16AL-A2	12	16	215	205	70	162		
MG LTX20-3	12	20	310	175	87	154		
MG LTX20-4	12	20	310	175	87	154		
MG L12-19	12	21	310	183	79	171		
MG LTX24H-3	12	24	335	205	87	162		
MG L60-N30-3	12	30	325	178	123	166		