



VIBRATION RESISTANT AGM
TECHNOLOGY

HVT

MOTORCYCLE BATTERIES

The HVT battery features a special battery casing capable of withstanding high temperatures. It has a significantly higher (starting) capacity and is extremely resistant to vibration due to the compressed AGM plate package making it ideal for Heavy V-Twin motorcycles. These motorcycles often have higher compression ratios and more available accessories, requiring significantly more power than similar SLA batteries.

power on command

- ⚡ Extreme resistance to vibration
- ⚡ Extreme heat proof
- ⚡ Extreme capacity and cranking performance

MODELS & SPECIFICATIONS

Article Number	Nominal Voltage (V)	Capacity Ah (10hr)	CCA	Length (mm)	Width (mm)	Height (mm)	Layout	Terminal
MH HVT-1	12	20	320	175	87	155		
MH HVT-2	12	32	450	169	131	175		
MH HVT-3	12	14	220	148	88	144		
MH HVT-4	12	22	325	173	99	153		
MH HVT-5	12	22	325	173	99	153		
MH HVT-6	12	23	350	203	88	162		
MH HVT-8	12	14	240	148	88	144		
MH HVT-10*	6	22	-	115	100	214		

*Please note that HVT-10 is a 6V conventional dry pre-charged battery without acid pack, suitable for classic Harley Davidson models.

HVT NANO-GEL TECHNOLOGY

MOTORCYCLE BATTERIES

Due to Nano-Gel-thickened electrolyte, it has lower self-discharge, and better resistance to deeper discharge making it perfect for motorcycles with additional power needs.

MODELS & SPECIFICATIONS

Article Number	Nominal Voltage (V)	Capacity Ah (10hr)	CCA	Length (mm)	Width (mm)	Height (mm)	Layout	Terminal
MH HVTG14H-3	12	14	220	149	87	144		
MH HVTG14H-4	12	14	220	149	87	144		
MH HVTG20H-3	12	19	290	176	87	154		
MH HVTG20H-4	12	19	290	176	87	154		
MH HVTG24H-3	12	24	410	205	87	162		
MH HVTG30H-3	12	30	430	166	130	175		