



LANDPORT B.V.

RAMGATSEWEG 63 | 4941 VN RAAMSDONKSVEER - THE NETHERLANDS

PHONE: +31 (0) 162 58 14 00 | FAX: +31 (0) 162 58 14 01

E-MAIL: INFO@LANDPORTBV.COM | WWW.LANDPORTBV.COM

01/09/2026

LP SERIES

MULTIPURPOSE AGM BATTERIES

VRLA AGM BATTERY

RELIABLE AND SAFE PERFORMANCE FOR MULTIPURPOSE APPLICATIONS.

The LP Series AGM batteries have been specially developed to be widely applicable. These lead acid batteries with AGM technology are completely sealed and therefore 100% maintenance free and leak-proof. These batteries have a low self-discharge. The reliable and safe multipurpose batteries from the LP Series offer a long service life and can be used in various industries.



FEATURES

- ABSORBENT GLASS MAT TECHNOLOGY
- RELIABLE AND SAFE PERFORMANCE
- LONG SERVICE LIFE - 3-5 YEARS IN STANDBY APPLICATION (AT 25°C)
- COMPLETELY SEALED AND 100% MAINTENANCE FREE
- VERY LOW SELF-DISCHARGE
- SUITABLE FOR MULTIPURPOSE APPLICATIONS
- VDS CERTIFICATION FOR THE SECURITY INDUSTRY



power on command



Powered by
LANDPORT
BATTERIES

www.landportbv.com

LP SERIES

MULTIPURPOSE AGM BATTERIES

MULTIPURPOSE APPLICATIONS

Reliable AGM batteries suitable for multipurpose applications in various industries: security (alarm systems, fire alarm systems and emergency lighting), backup power / uninterruptible power supply (UPS), medical & healthcare (patient lifts, stairlifts and bath lifts), telecommunication systems, green energy systems (solar and wind energy) and hobby (electric scooters).



“VdS certificates guarantee reliability and safety. Essential in the security industry and therefore also for our batteries.”

MODELS AND SPECIFICATIONS

Article number	Voltage (V)	Capacity (Ah@20hr)	Capacity (Ah@5hr)	Length (mm)	Width (mm)	Height (mm)	Total Height (mm)	Layout	Terminal	VdS-certified
VRLA LP06001,2 T1	6	1.2	1.0	97	24	52	57		T1	-
VRLA LP06002,8 T1	6	2.8	2.4	66	33	98	103		T1	-
VRLA LP06003,2 T1	6	3.2	2.8	134	34	61	66		T1	-
VRLA LP06004,5 T1	6	4.7	4.1	70	47	100	105		T1	-
VRLA LP06006 T1	6	5.9	5.1	70	47	100	106		T1	-
VRLA LP06007 T1	6	7.5	6.5	151	35	93	99		T1	-
VRLA LP06012 T1V	6	11.9	10.6	151	50.5	94	100		T1	VdS
VRLA LP12000,8	12	0.8	0.7	96	25	62	62	-	T20	-
VRLA LP12001,2 T1	12	1.2	1.2	97	43	52	58		T1	VdS
VRLA LP12002,3 T1V	12	2.3	2.0	178	35	60	66		T1	VdS
VRLA LP12002,9 T1	12	2.9	2.4	79	58	98	103		T1	-
VRLA LP12003,4 T1V	12	3.2	2.8	134	67	59.5	65.5		T1	VdS
VRLA LP12004L T1	12	4.0	3.4	195	47	70	76		T1	-
VRLA LP12004,5 T1	12	4.7	4.0	91	70	102	107		T1	-
VRLA LP12005,4 T1V	12	5.3	4.7	90	70	101	107		T1	VdS
VRLA LP12005,4 T2V	12	5.3	4.7	90	70	101	107		T2	VdS
VRLA LP12007 T1V	12	7.4	6.5	151	65	94	99.5		T1	VdS
VRLA LP12007 T2V	12	7.4	6.5	151	65	93.5	99		T2	VdS
VRLA LP12007,2 T1V	12	7.9	7.0	152	65.5	94.5	100		T1	VdS
VRLA LP12007,2 T2V	12	7.9	7.0	152	65.5	94.5	100		T2	VdS
VRLA LP12009 T1	12	9.2	8.0	151	65	94	100		T1	-
VRLA LP12009 T2	12	9.2	8.0	151	65	94	100		T2	-
VRLA LP12010H T2	12	9.9	8.7	151	65	111	117		T1	-



Article number	Voltage (V)	Capacity (Ah@20hr)	Capacity (Ah@5hr)	Length (mm)	Width (mm)	Height (mm)	Total Height (mm)	Layout	Terminal	VdS-certified
VRLA LP12012 T2	12	12.7	10.7	152	99	95	100		T2	-
VRLA LP12012 T2V	12	12.0	10.2	152	98	95	102		T2	VdS
VRLA LP12018 T12V	12	19.8	17.2	181.5	77	167.5	167.5		T12	VdS
VRLA LP12018 T3V	12	19.8	17.2	181.5	77	167.5	167.5		T3	VdS
VRLA LP12020 T3	12	20.2	17.3	182	77	167	167		T3	-
VRLA LP12024 T12V	12	23.8	19.9	166	175	125	125		T12	VdS
VRLA LP12026 T12V	12	25.8	21.9	166.5	175	125	125		T12	VdS
VRLA LP12028 T3	12	28.3	24.1	166	175	126	126		T3	-
VRLA LP12033 T6	12	34.6	28.8	196	130	155	170		T6	-
VRLA LP12040 T6V	12	40	34.6	197	165	170	170		T6	VdS
VRLA LP12045 T6V	12	42	35	197	165	170	170		T6	VdS
VRLA LP12050 T6	12	47	38.9	198	167	173	173		T6	-
VRLA LP12055 T6	12	52.6	45.5	257	132	200	200		T6	-
VRLA LP12060 T6	12	57.8	47.5	230	139	210	215		T6	-
VRLA LP12065 T6V	12	68.2	59	348	167	178	178		T6	VdS
VRLA LP12080H T6	12	81.8	66.6	260	169	213	219		T6	-
VRLA LP12100 T11	12	105	86	330	172	218	223		T11	-
VRLA LP12120 T11	12	125.9	103.8	406	173	225	234		T11	-
VRLA LP12150 T11	12	157.6	13.5	481	170	241	245		T11	-
VRLA LP12200 T11	12	209.8	174	522	240	221	226		T11	-
VRLA LP12250 T11	12	262	221	522	268	220	225		T11	-

