

MARINE

LEISURE BATTERIES

**RELIABLE STARTING POWER.
LIGHT CYCLIC APPLICATIONS.**

Dynac Marine is a starter battery with flooded calcium technology which is designed to perform on the water. This sealed maintenance free battery with V3 vibration resistance is spill-proof and safe in use. Besides starting engines, Dynac Marine is ideal for marine and leisure vehicles with light power consumers such as bow and interior lightning, thrusters and other on-board equipment such as radio and depth gauge. Available in a range of batteries from 120Ah to 225Ah.



FEATURES






- FLOODED CALCIUM TECHNOLOGY
- RELIABLE STARTING POWER
- SEALED MAINTENANCE FREE (SMF)
- VIBRATION RESISTANCE V3
- SPILL-PROOF, SAFE IN USE
- RECOMMENDED FOR MARINE AND LEISURE VEHICLES WITH LIGHT POWER CONSUMERS.

power on command



MARINE


MODELS & SPECIFICATIONS

Model	Article number	Voltage (V)	Capacity (Ah)	CCA A (EN)	Box type	Length (mm)	Width (mm)	Height (mm)	Total height (mm)	Layout	Terminal	Hold-down
62034 DIN	LMFM 62034 DIN	12	120	680	A	510	188	193	216		1	-
64020 DIN	LMFM 64020 DIN	12	140	760	A	510	188	193	216		1	-
66514 DIN	LMFM 66514 DIN	12	170	950	B	510	221	193	216		1	-
68034 DIN	LMFM 68034 DIN	12	180	1000	B	510	221	193	216		1	-
72511 DIN	LMFM 72511 DIN	12	225	1150	C	515	274	217	240		1	-

BATTERY CLASSIFICATIONS AS PER EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance level
W3	C2	V3	E1

TERMINAL 1



CARE & MAINTENANCE

Maintain your battery with a smart automatic charger by GYS. For MARINE batteries we advise the following battery chargers depending on the capacity of your battery (Ah).

Model	Specs	Description	Battery range (Ah)
BATIUM 15-24	6/12/24V 7/10/15A	GYS smart automatic charger	35-225
BATIUM 25-24	6/12/24V 7/15/25A	GYS smart automatic charger	35-350

