



intAct Bike-Power AGM-HVT

Sealed maintenance-free AGM battery with heavily compressed plate packs | electrolyte absorbed in glass fibre separators



intAct **Bike-Power AGM-HVT**

Extremely vibration-resistant design

The durable energy bundle absorbs the strongest shocks from Harleys and other high-capacity bikes and also starts two-wheelers with high electrical energy requirements (e.g. with ABS).

Our recommendation for motorcycles that need a lot of starting power and of course with strong vibrations.

CHARACTERISTICS

- » **Perfect for Harleys** and other bikes with **high-capacity 2-cylinder engines**.
- » **Highest cold cranking amper:** For two-wheelers with high energy requirements, e.g. due to ABS safety technology.
- » **Extremely vibration-resistant.** Plate packs compressed and precisely fitted into the battery box.
- » **Robust housing made of impact-resistant plastic.**
For heavy mechanical stress.
- » **Leak-proof. Can be installed at an angle,** as the electrolyte is absorbed in glass fibre mat.
- » **Sealed maintenance-free.**
- » **Can withstand the strongest vibrations.**
- » **Safely stored grids** thanks to swollen glass fibre mat separators (AGM).
- » **Wet charged.** Except HVT-10: It comes dry-charged, an acid pack is not included.

LANDPORT
BATTERIES

Ramgatseweg 63 // NL - 4941 VN Raamsdonksveer
Phone: +31 (0) 162 58 14 00 // Fax: +31 (0) 162 58 14 01
info@landportbv.com // www.landportbv.com

intAct
BATTERY - POWER

ALWAYS THE
BATTERY
THAT FITS!

intAct Bike-Power AGM HVT

Sealed maintenance-free AGM battery with heavily compressed plate packs | electrolyte absorbed in glass fibre separators

Item Nr.	Volt	Capacity	Cold cranking ampere	Length mm	Width mm	Height mm	Position of Terminal	Terminal	Base plate	Degassing	Weight/ kg
IH HVT-01	12	20 Ah (c20)	350 A (EN)	175	87	155	0	M	–	–	6,5
IH HVT-02	12	30 Ah (c20)	380 A (EN)	169	131	174	0	M	–	–	10,2
IH HVT-03	12	14 Ah (c20)	250 A (EN)	150	87	145	0	Connection screws	–	–	5
IH HVT-08	12	14 Ah (c20)	250 A (EN)	150	87	145	1	Connection screws	–	–	4,9
IH HVT-10*	6	22 Ah (c20)	300 A (EN)	115	100	214	1	I	–	–	3,1

* Note HVT-10: Dry pre-charged, an acid pack is not supplied.

