

SCB90 Pro Jump Starter 24v



The **SC POWER SCB90 Pro 24** is a 9.0 Ah Lithium Jump Starter with BMS for the professional. Designed to be compact, lightweight and powerful.

The **SCB90 Pro 24** is designed based on "safety first". We have a patent pending designed Battery Management System "BMS", which protects the unit against overcharge, overheating, over discharge, reverse polarity, sparks, short-circuit and all this comes in a flame retardant case.



The **SCB90Pro24** is our "High Performance" model developed in particular for trucks (24V).

- Ultra compact, lightweight (2050 gr) and powerful, it starts diesel engines up to 13L.
- Equipped with a LED flashlight with a SOS strobe function, it provides additional night time safety warning to other motorist.
- Supplied with a thermoformed high-end storage bag, a hook for hanging and a rubber protective cover.



LED Lighting



Hook for hanging



www.sc-power.eu

SCB90 Pro Jump Starter 24v

Internal Battery	Lithium Ion Polymer Batteries
Peak Current	1000 A
Output Voltage	24 v (9 Ah)
USB Output 2.0	No
Memory Data Saver	No
Battery Charge Indicator	Yes
LED Lighting	Yes
« Weak Battery » Function	A Manual override is provided for increased starting capacity for highly discharged batteries
Safety features	<ul style="list-style-type: none"> • Male/Female connector to avoid wrong connection • Isolated and strengthened clamps • Cable bypass in clamps to distribute the current during jump starts • Patented Battery Management System (electronic system to manage the Lithium cells) • 94-V0 Flame retardant case • Protections against overcharge, overheat, deep discharge, reverse polarity, sparks, short-circuit, improper handling, ...
Certifications	CE RoHS
Recharge Time at 20°C	40 min
Charge intervals between recharges	Up to 1 year
Jump Start capacity after full charge	Up to 10 jump starts, depending on battery state of charge, age and maintenance status of the vehicle, ...
Applications	Jump starts all vehicles equipped with 24 V lead acid batteries up to 13 L diesel
Net Weight	2050 gr
Dimensions	L 190 mm x w 210 mm x h 60 mm
Cable Section	16 mm ²
Cable Length	400 mm
Carry handle	Yes
Supplied with	Thermoformed storage bag and accessories, rubber protective cover
Hook for hanging	Yes

