



ABSORBENT GLASS MAT TECHNOLOGY

# SLA

## MOTORCYCLE BATTERIES

This AGM battery is activated from the production process, making it operational immediately after purchase. Aside from periodic charging, no further maintenance is necessary. This leak-proof battery can be mounted at a 90° angle. Ideal for motorcycles and powersport vehicles on rough terrain and in all weather conditions such as all-terrain vehicles, jet-skis and snowmobiles.

power on command

- ⚡ Super safe & ready to use
- ⚡ Super capacity and cranking performance
- ⚡ Super resistance to vibrations up to 90° angle positioning

## MODELS & SPECIFICATIONS

Article Number	Nominal Voltage (V)	Capacity Ah (10hr)	CCA	Length (mm)	Width (mm)	Height (mm)	Layout	Terminal
MS 6N4B-2	6	4	50	101	47	95		
MS 6N4-2	6	4	30	71	71	93		
MS 6N6-3	6	6	65	95	55	117		
MS B49-6	6	10	90	91	83	159		
MS 6N11A	6	11	100	121	58	130		
MS B38-6A	6	13	110	119	83	161		
MS LT4B-5	12	2,3	40	113	38	87		
MS LTR4A-S	12	2,3	45	114	49	86		
MS LB3-3	12	3	35	98	56	109		
MS LTX5-3	12	4	80	113	70	105		
MS LB5-3	12	5	70	118	59	129		
MS SLA 12-4S	12	5	55	113	70	85		
MS LTX7-3	12	6	100	113	70	128		
MS LTX7A-4	12	6	105	150	84	94		
MS LTZ7-S	12	6	130	113	70	105		
MS LT7B-4	12	6,5	110	150	65	93		
MS LB7-3	12	7	90	135	76	122		
MS LB7-4	12	7	90	135	76	122		
MS LTZ7V	12	7	110	113	70	120		
MS LTZ8V	12	7	120	113	70	128		
MS LT9B-4	12	8	120	150	70	104		
MS LTX9-4	12	8	135	150	84	104		
MS LTZ10-S	12	8,6	190	151	87	95		
MS LTX9A-3	12	9	120	135	76	131		
MS LTX9A-4	12	9	120	135	76	131		
MS LT12-102	12	10	120	194	59	112		
MS LB10-3	12	10	135	135	90	145		
MS LT12B-4	12	10	160	150	70	130		
MS LTX12-4	12	10	180	151	87	130		
MS LTX12A-4	12	10	175	151	87	105		
MS LTZ12-S	12	11	210	151	87	110		
MS LTZ14-S	12	11,2	220	151	87	110		
MS LB12A-3	12	12	155	134	80	160		
MS LB12A-4	12	12	155	134	80	160		



## MODELS & SPECIFICATIONS

Article Number	Nominal Voltage (V)	Capacity Ah (10hr)	CCA	Length (mm)	Width (mm)	Height (mm)	Layout	Terminal
MS LT14B-4	12	12	180	150	70	144		
MS LTX14-3	12	12	200	151	87	145		
MS LTX14-4	12	12	200	151	87	145		
MS LTX14AH-3	12	14	200	135	90	168		
MS LTX14AH-4	12	14	200	135	90	168		
MS LTX16-4	12	14	230	151	87	160		
MS LTX20-3	12	18	270	177	88	154		
MS LTX20-4	12	18	270	177	88	154		
MS LB16CL-B (S)	12	19	260	175	100	174		
MS LTX20CH-4	12	19	275	151	87	162		
MS LTX24H-3	12	21	320	205	87	162		
MS SLA 12-22	12	22	250	181	76	167		
MS L60-N30-3	12	30	300	178	123	166		
MS L60-N30-4	12	30	300	178	123	166		
MS LTX30L	12	30	385	166	126	175		

## RECOMMENDED BATTERY CHARGER

Article Number	Brand	Voltage	Current	Range (Ah) @12V
PS SC10	SC Power	6/12V	1A	5-20
PS SC38	SC Power	6/12V	0,8/3,8A	1.2-60



**LANDPORT B.V.**

RAMGATSEWEG 63 | 4941 VN RAAMSDONKSVEER - THE NETHERLANDS

PHONE: +31 (0) 162 58 14 00 | FAX: +31 (0) 162 58 14 01

E-MAIL: [INFO@LANDPORTBV.COM](mailto:INFO@LANDPORTBV.COM) | [WWW.LANDPORTBV.COM](http://WWW.LANDPORTBV.COM)