

CLASSIC

AUTOMOTIVE BATTERIES

**ORIGINAL DESIGN.
OLD-FASHIONED HARD RUBBER CASING.**

Dynac Classic is a starter battery which is suitable for classic vehicles such as oldtimers and vintage cars. This battery is produced according to flooded low antimony technology and delivers durable and powerful performance. Most models come in an original hard rubber casing and can be delivered either dry pre-charged or wet charged (on request). Available in a range of 6V and 12V batteries from 66Ah to 200Ah.



FEATURES

- FLOODED LOW ANTIMONY TECHNOLOGY
- DURABLE AND POWERFUL PERFORMANCE
- ORIGINAL HARD RUBBER CASING
- AVAILABLE AS DRY PRE-CHARGED OR WET CHARGED
- SUITABLE FOR ALMOST ALL CLASSIC VEHICLES

+

power on command



DRY CHARGED

MODELS & SPECIFICATIONS

Model	Article number	Voltage (V)	Capacity (Ah)	CCA A (EN)	Box type	Length (mm)	Width (mm)	Height (mm)	Total height (mm)	Layout	Terminal	Hold-down
06612	ACLPV 06612HR	6	66	360	-	186	175	166	188		1	-
07715	ACLPV 07715HR	6	77	490	-	215	170	166	191		1	-
08411	ACLPV 08411HR	6	84	460	-	225	173	195	220		1	-
10011	ACLPV 10011HR	6	100	520	-	225	173	195	220		1	-
11213	ACLPV 11213HR	6	112	610	-	503	98	193	225		1	-
57016	ACLPV 57016HR	12	70	510	-	490	110	195	220		1	-

BATTERY CLASSIFICATIONS AS PER EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance level
W2	C2	V2	E2

WET CHARGED

MODELS & SPECIFICATIONS

Model	Article number	Voltage (V)	Capacity (Ah)	CCA A (EN)	Box type	Length (mm)	Width (mm)	Height (mm)	Total height (mm)	Layout	Terminal	Hold-down
06612	ACLPV 06612HRN	6	66	360	-	186	175	166	188		1	-
07715	ACLPV 07715HRN	6	77	490	-	215	170	166	191		1	-
08411	ACLPV 08411HRN	6	84	460	-	225	173	195	220		1	-
10011	ACLPV 10011HRN	6	100	520	-	225	173	195	220		1	-
11213	ACLPV 11213HRN	6	112	610	-	503	98	193	225		1	-
14023*	ACLPV 14023N**	6	140	900	M04	257	175	216	235		1	B1
16022*	ACLPV 16022N	6	165	900	M05	328	171	211	233		1	-
22013*	ACLPV 22013N	6	200	1000	M06	393	171	231	231		1	-
57016	ACLPV 57016HRN	12	70	510	-	490	110	195	220		1	-


* polypropylene casing instead of hard rubber casing

** flooded hybrid technology instead of flooded low antimony technology


BATTERY CLASSIFICATIONS AS PER EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance level
W2	C2	V2	E2

TERMINAL 1



HOLD-DOWN B1



CARE & MAINTENANCE

Maintain your battery with a smart automatic charger by GYS. For CLASSIC batteries we advise the following battery chargers depending on the capacity of your battery (Ah).

Model	Specs	Description	Battery range (Ah)
BATIUM 7-24	6/12/24V 3/7A	GYS smart automatic charger	15-130
BATIUM 15-24	6/12/24V 7/10/15A	GYS smart automatic charger	35-225

