


 BIKE  
 POWER **SLA**
**Sealed maintenance-free AGM battery**

Electrolyte held in Absorbent Glass Mat separators | Wet charged



Mountable in tilted position.

**intact**  
 BATTERY - POWER

## READY-TO-USE ALL-ROUNDER.

Withstands the frequent charging during seasonal use and over many short distances cycles slightly better than conventional flooded batteries, and also starts reliably when not fully charged.

### GENERAL FEATURES

- » **High power reserve.** Significant starting power even when partially discharged.
- » **Shake-proof.** The plates are firmly embedded in the glass fibre mat.
- » **Sealed maintenance-free.** Refilling is not possible and not necessary, because the firmly sealed battery loses virtually no liquid due to gas recombination.
- » **Not well suited for repeated deep discharging** (below 10.5 V).
- » **Leak-proof.** The battery can also be installed at an angle, as the electrolyte is held in a glass fibre mat and the battery is tightly sealed.
- » **Wet charged. Ready to use.**

## AGM/SLA

Thanks to the Absorbent Glass Mat technology, in which the acid is bound into mat of fibres, these batteries are completely maintenance-free, i.e. once the battery has been filled for the first time, it doesn't have to be opened again. It is less sensitive to vibration than the classic battery, brings a higher degree of safety and is ideal for vehicles used all-year-round. AGM batteries are pre-charged dry and delivered with a special acid pack, as a result of which they can be stored almost indefinitely.





### YOUR BENEFITS AS A DEALER

- » **The affordable all-rounder for many applications.**
- » **Wet charged.** Can be stored for at least 9 months.

**OUR BEST CHOICE AT A FAIR PRICE.**

Battery	Volt (V)	Capacity Ah	CCA EN	Length mm	Width mm	Height mm	Layout	Terminal
IS CT4B-5	12	2,3 AH (c20)	50 A (EN)	114	39	86	4	K
IS CTZ5-S	12	4 AH (c20)	50 A (EN)	113	70	85	0	A
IS CB5-3	12	5 AH (c20)	70 A (EN)	119	59	130	0	B
IS CTX7A-BS	12	6 AH (c20)	80 A (EN)	150	87	93	1	A
IS CTZ7-S	12	6 AH (c20)	80 A (EN)	113	70	105	0	A
IS CT7B-4	12	6,5 AH (c20)	80 A (EN)	150	66	93	1	A
IS CTZ8V	12	7 AH (c20)	120 A (EN)	114	70	130	0	A
IS CT9B-4	12	8 AH (c20)	100 A (EN)	150	70	105	1	A
IS CTX9-BS	12	8 AH (c20)	120 A (EN)	150	87	105	1	A
IS CTZ10-S	12	8,5 AH (c20)	140 A (EN)	150	88	93	1	A
IS CT12B-4	12	10 AH (c20)	150 A (EN)	150	70	130	1	A
IS CTZ12-S	12	11 AH (c20)	190 A (EN)	150	88	110	1	A
IS CTZ14-S	12	11,5 AH (c20)	200 A (EN)	150	88	110	1	A
IS CT14B-4	12	12 AH (c20)	190 A (EN)	150	70	145	1	A
IS CTX14-BS	12	12 AH (c20)	180 A (EN)	150	87	147	1	A
IS SLA 12-22	12	22 AH (c20)	230 A (EN)	181	76	167	0	G
IS CTX30L-BS	12	30 AH (c20)	360 A (EN)	166	126	175	0	A

### TERMINAL



### LAYOUT

