



Since 1993



SLA | SMF | DRY
TECHNOLOGY

L&G

LAWN & GARDEN BATTERIES

Our batteries for lawn and garden machinery are engineered to thrive in the harshest terrains and endure the most demanding outdoor conditions. Designed for year-round performance, our lawn and garden batteries deliver power not only in spring but also withstand the challenges of hot summers and freezing winters. Our extensive range provides reliable and robust cold cranking amps, ensuring efficient starts for lawn mowers, lawn tractors/riding mowers and various other garden machinery. Available in 12V series, including SLA, SMF, and DRY (with acid pack), our batteries serve a wide range of applications.

WWW.LANDPORTBV.COM

SLA



This AGM battery is activated from the production process, making it operational immediately after purchase. Aside from periodic charging, no further maintenance is necessary. This leak-proof battery can be mounted at a 90° angle. This battery is extremely resistant to vibration due to the compressed AGM plate package making it ideal for the rough terrain where the mini tractors have to operate in.

Article Number	Nominal Voltage (V)	Capacity Ah (10hr)	CCA	Length (mm)	Width (mm)	Height (mm)	Total Height (mm)	Layout	Terminal
LS SLA 12-20A	12	20	200	181	76	167	167		
LS U1-280 SLA	12	24	280	197	130	159	170		
LS U1R-280 SLA	12	24	280	197	130	159	170		

SMF



Due to the Calcium adaptive this SMF battery has numerous advantages such as low water consumption, higher starting power, longer service life and lower self discharge. The SMF battery is activated from the production process, making it operational immediately after purchase. Aside from periodic charging, no further maintenance is necessary.

Article Number	Nominal Voltage (V)	Capacity Ah (10hr)	CCA	Length (mm)	Width (mm)	Height (mm)	Total Height (mm)	Layout	Terminal
LB U1-250MF	12	21	250	196	132	159	185		
LB U1-R250MF	12	21	250	196	132	159	185		
LB U1-300MF	12	24	300	196	132	159	185		
LB U1-R300MF	12	24	300	196	132	159	185		

DRY (with acid pack)



Proven by advanced technology. Batteries that meet basic starting needs, which require maintenance during use by topping up with demineralized water. The battery is activated when filled with electrolyte, acid package included. Due to the separate acid package, it can be stored for an extended period before being put into use.

Article Number	Nominal Voltage (V)	Capacity Ah (10hr)	CCA	Length (mm)	Width (mm)	Height (mm)	Total Height (mm)	Layout	Terminal
LB 12N18-3A*	12	18	165	205	90	162	162		
LD 12N24-3	12	24	220	184	124	175	175		
LD 12N24-4	12	24	220	184	124	175	175		

*Acid packaging not included.

RECOMMENDED BATTERY CHARGER

Article Number	Brand	Voltage	Current	Range (Ah) @12V
PS SC10	SC Power	6/12V	1A	5-20
PS SC38	SC Power	6/12V	0,8/3,8A	1.2-60