



Since 1993



ABSORBENT GLASS MAT TECHNOLOGY AGM

MOTORCYCLE BATTERIES

By using 'Absorbent Glass Mat', the electrolyte is absorbed in a more solid form within the battery. As a result, it has a higher (starting) capacity compared to an equivalent DRY type battery. Additionally, this battery can be mounted at an angle, and it doesn't require topping up with water due to its closed system. The battery is activated when filled with electrolyte (a suitable acid package is included). Therefore, it can be stored for an extended period before being put into use.

power on command

- ⚡ Super capacity and cranking performance
- ⚡ Super robust and vibration resistance
- ⚡ OEM compatible



MODELS & SPECIFICATIONS

Article Number	Nominal Voltage (V)	Capacity Ah (10hr)	CCA	Length (mm)	Width (mm)	Height (mm)	Layout	Terminal
MA LT4B-BS	12	2,3	40	113	38	85		
MA LTR4A-BS	12	2,3	45	113	48	85		
MA LTX4L-BS	12	3	50	113	70	85		
MA LTX5L-BS	12	4	80	113	70	105		
MA LTX7A-BS	12	6	105	150	87	93		
MA LTX7L-BS	12	6	100	113	70	130		
MA LTZ7S-BS	12	6	130	113	70	105		
MA LT7B-BS	12	6,5	90	150	66	93		
MA LT9B-BS	12	8	115	150	70	105		
MA LTX9-BS	12	8	135	150	87	105		
MA LTZ10S-BS	12	8,6	190	150	88	93		
MA LTX9A-BS	12	9	120	135	75	139		
MA LT12A-BS	12	10	175	150	88	105		
MA LT12B-BS	12	10	175	150	70	130		
MA LTX12-BS	12	10	180	150	87	130		
MA LTZ12S-BS	12	11	210	150	88	110		
MA LTZ14S-BS	12	11,2	220	150	88	110		
MA LT14B-BS	12	12	150	150	70	145		
MA LTX14-BS	12	12	200	150	87	145		
MA LTX14L-BS	12	12	200	150	87	145		
MA LTX14AH-BS	12	12	210	133	90	164		
MA LTX14AHL-BS	12	12	210	133	90	164		
MA LTX15L-BS	12	13	210	174	87	130		
MA LTX16-BS	12	14	230	150	87	161		
MA LTX16-BS-1	12	14	230	150	87	161		
MA LTX20-BS	12	18	240	175	87	155		
MA LTX20L-BS	12	18	240	175	87	155		
MA LTX20CH-BS	12	18	270	150	87	161		
MA LTX20HL-BS	12	18	310	175	87	155		
MA LTX24HL-BS	12	21	330	205	87	162		

RECOMMENDED BATTERY CHARGER

Article Number	Brand	Voltage	Current	Range (Ah) @12V
PS SC10	SC Power	6/12V	1A	5-20
PS SC38	SC Power	6/12V	0,8/3,8A	1.2-60