



Since 1993



ABSORBENT GLASS MAT TECHNOLOGY

SLA

MOTORCYCLE BATTERIES

This AGM battery is activated from the production process, making it operational immediately after purchase. Aside from periodic charging, no further maintenance is necessary. This leak-proof battery can be mounted at a 90° angle. Ideal for motorcycles and powersport vehicles on rough terrain and in all weather conditions such as all-terrain vehicles, jet-skis and snowmobiles.

power on command

- ⚡ Super safe & ready to use
- ⚡ Super capacity and cranking performance
- ⚡ Super resistance to vibrations up to 90° angle positioning

SLA

MOTORCYCLE BATTERIES



Since 1993

MODELS & SPECIFICATIONS

Article Number	Nominal Voltage (V)	Capacity Ah (10hr)	CCA	Length (mm)	Width (mm)	Height (mm)	Layout	Terminal
MS 6N4B-2	6	4	50	101	47	95		
MS 6N4-2	6	4	30	71	71	93		
MS 6N6-3	6	6	65	95	55	117		
MS B49-6	6	10	90	91	83	159		
MS 6N11A	6	11	100	121	58	130		
MS B38-6A	6	13	110	119	83	161		
MS LT4B-5	12	2,3	40	113	38	86		
MS LTR4A-S	12	2,3	45	113	48	85		
MS LB3-3	12	3	20	98	56	110		
MS LTX5-3	12	4	80	113	70	105		
MS LB5-3	12	5	65	119	59	130		
MS SLA 12-4S	12	5	55	113	70	85		
MS LTX7-3	12	6	100	113	70	130		
MS LTX7A-4	12	6	105	150	87	93		
MS LTZ7-S	12	6	130	113	70	105		
MS LT7B-4	12	6,5	90	150	66	93		
MS LB7-3	12	7	80	137	75	124		
MS LB7-4	12	7	80	137	75	124		
MS LTZ8V	12	7	120	113	70	130		
MS LT9B-4	12	8	115	150	70	105		
MS LTX9-4	12	8	135	150	87	105		
MS LTZ10-S	12	8,6	190	150	88	93		
MS LTX9A-3	12	9	120	135	75	138		
MS LTX9A-4	12	9	120	135	75	138		
MS LB10-3	12	10	160	134	89	145		
MS LT12B-4	12	10	175	150	70	130		
MS LTX12-4	12	10	180	150	87	130		
MS LTX12A-4	12	10	175	150	88	105		
MS LTZ12-S	12	11	210	150	88	110		
MS LTZ14-S	12	11,2	220	150	88	110		
MS LB12A-3	12	12	165	135	80	160		
MS LB12A-4	12	12	165	135	80	160		
MS LT14B-4	12	12	175	150	70	145		
MS LTX14-3	12	12	200	150	87	146		

MODELS & SPECIFICATIONS

Article Number	Nominal Voltage (V)	Capacity Ah (10hr)	CCA	Length (mm)	Width (mm)	Height (mm)	Layout	Terminal
MS LTX14-4	12	12	200	150	87	146		
MS LTX14AH-3	12	14	210	134	89	166		
MS LTX14AH-4	12	14	210	134	89	166		
MS LTX16-4	12	14	230	150	87	163		
MS LTX20-3	12	18	310	175	87	155		
MS LTX20-4	12	18	310	175	87	155		
MS LB16CL-B (S)	12	19	260	175	100	175		
MS LTX20CH-4	12	19	320	150	87	163		
MS LTX18-3	12	21	350	205	85	162		
MS LTX24H-3	12	21	350	205	85	162		
MS SLA 12-22	12	22	250	181	76	167		
MS L60-N30-3	12	30	300	179	125	166		
MS L60-N30-4	12	30	300	179	125	166		
MS LTX30L	12	30	385	166	126	173		

RECOMMENDED BATTERY CHARGER

Article Number	Brand	Voltage	Current	Range (Ah) @12V
PS SC10	SC Power	6/12V	1A	5-20
PS SC38	SC Power	6/12V	0,8/3,8A	1.2-60



LANDPORT B.V.

RAMGATSEWEG 63 | 4941 VN RAAMSDONKSVEER - THE NETHERLANDS

PHONE: +31 (0) 162 58 14 00 | FAX: +31 (0) 162 58 14 01

E-MAIL: INFO@LANDPORTBV.COM | WWW.LANDPORTBV.COM