



EFB 560500056 EAN CODE: 8717101025154

Description

Dynac Start-Stop EFB is a range of start-stop batteries with EFB technology delivering reliable starting power and high performance. This battery offers a 2 times greater cycle resistance compared to a standard battery. This battery is the perfect choice for vehicles with multiple power consumers and basic start-stop systems. Available in a range of 12V batteries from 40Ah to 110Ah with a wide car park coverage for European and Asian vehicles.

Performance

Nominal Voltage	12
Capacity	60Ah (20hr, 1.75V/cell)
CCA EN	560

Dimensions / Casing / Weight		
Вох Туре	L2	
	Length: 242 mm	
Dimensions	Width: 174 mm	
Dimensions	Height: 189 mm	
	Total Height: 189 mm	
Net Weight	17.1 Kg	
Acid Volume	4.8	
Material Casing / Lid	Polypropylene	

Technical Characteristics Technology Flooded Calcium Seperator PE



Features

- Enhanced Flooded Battery technology
- Reliable starting power, high performance
- 2 times longer cycle life compared to conventional batteries
- Range of 10 models, wide car park coverage (EU and Asia)
- 100% maintenance free, leakproof, save handling
- Eco-friendly product and 99% recyclable

Layout	Terminal	Hold-down
- +	$ \begin{array}{c} \bullet & \emptyset & 19,5 \\ \hline \bullet & & & \bullet & \emptyset & 17,9 \\ \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \hline \bullet & & & & \bullet & & \bullet \\ \hline \bullet & & & & \bullet \\ \hline \bullet & & & & \bullet \\ \hline \bullet $	100 max

ater Consumption	Charge Retention	Vibration Resistance	Endurance Level	Micro-Cycle Performance
/4	C2	V3	-	M2

(Note) All above information shall be changed without prior notice, Landport Batteries reserves the right to explain and update the latest information.

www.landportbv.com