



# intAct Bike-Power GEL

Sealed maintenance-free GEL battery | electrolyte thickened into a gel-like mass | wet charged | absolutely maintenance-free

Art.No.

## IG CTX4L-BS

Japancode

YTX4L-BS, YTZ4V, YTZ5S, YTX4L

<b>Volt</b>	12V
<b>Capacity</b>	3 Ah (c20)
<b>CCR -18°C(EN)</b>	60 A (EN)
<b>Electrolyte</b>	diluted sulphuric acid
<b>Size (LxWxH)</b>	113 x 70 x 85 mm
<b>Weight</b>	1,8 kg
<b>Pos. of Terminal</b>	0
<b>Terminal</b>	A
<b>Base plate</b>	-

### Usage




### For heavy loads, including ABS

Delivers 30% more starting power for modern motorcycles with many electrical consumers and covers consumption peaks. Low self-discharge, bike starts reliably even after up to 3 months. Our recommendation if many consumers are installed or the motorcycle is rarely used.


- » **Even more cycle-resistant** than Bike-Power AGM and Bike-Power SLA of the same box size.
- » **Low self-discharge.** For seasonal use.
- » **Very high vibration-resistance.** Electrolyte thickened into a gel-like mass.
- » **30% more starting power** than a conventional battery of the same box size. For motorcycles with many consumers, including ABS.
- » **Sealed maintenance-free** battery. Refilling is neither possible nor necessary.
- » Wet charged. **Ready to use.**



Size



Pos. of Terminal 0



Terminal A



Base plate -