#### **Motorcycle Batteries**



#### intAct Bike-Power GEL

Sealed maintenance-free GEL battery | electrolyte immobilized by gel-additive | wet charged



POW

## FOR HEAVY LOADS, INCLUDING ABS

Delivers 30% more starting power for modern motorcycles with many electrical consumers and covers consumption peaks. Low self-discharge, bike starts reliably even after up to 3 months. Our recommendation if many consumers are installed or the motorcycle is rarely used.

- » Even more cycle-resistant than Bike-Power AGM and Bike-Power SLA of the same box size.
- » Low self-discharge. For seasonal use.
- » Very high vibration-resistance. Electrolyte immobilized by geladditive.
- » 30% more starting power than a conventional battery of the same box size. For motorcycles with many consumers, including ABS.
- » Sealed maintenance-free battery. Refilling is neither possible nor necessary.
- » Wet charged. **Ready to use.**

## Datasheet



Artnum.

Japan-Code

# IG YT10B-4


CT10B-4, CTZ10-S

| Volt                | 12V  |
|---------------------|--|
| Capacity            | 8,5 AH (c20)   |
| CCR - 18°C (EN)     | 200 A (EN)   |
| Electrolyte         | diluted sulphuric acid   |
| Electrolyte density | 1,28 +/- 0,01 kg/l (25°)   |
| Size (LxWxH)        | 150 x 87 x 94 mm   |
| Weight              | 3,1 kg   |
| Pos. of Terminal    |  |
| Technology          | Sealed maintenance-free GEL battery   electrolyte<br>immobilized by gel-additive   wet charged |
| Terminal            | J<br>FRONT   |

-

121/

PORTE CELLE PORTE CELLE PORTE CELLE PORTE CELLE



Base plate



Landport Batteries Ramgatseweg 63 4941VN Raamsdonksveer

+31 (0) 162 58 14 00 www.landportbv.com