Motorcycle Batteries



intAct Bike-Power HVT

Sealed maintenance-free AGM battery with heavily compressed plate packs | electrolyte held in glass fibre separators













EXTREMELY VIBRATION-RESISTANT DESIGN

The durable energy bundle absorbs the strongest shocks from Harleys and other high-capacity bikes and also starts two-wheelers with high electrical energy requirements (e.g. with ABS). Our recommendation for motorcycles that need a lot of starting power and of course with strong vibrations.


- » Perfect for Harleys and other bikes with high-capacity 2cylinder engines.
- » Highest cold cranking amper: For two-wheelers with high energy requirements, e.g. due to ABS safety technology.
- **Extremely vibration-resistant.** Plate packs compressed and precisely fitted into the battery box.
- » Robust housing made of impact-resistant plastic. For heavy mechanical stress.
- » Leak-proof. Can be installed at an angle, as the electrolyte is held in glass fibre mat.
- » Sealed maintenance-free.

Datasheet



Artnum.	IH HVT-10
Japan-Code	CB2-6, 66006-29F
Volt	6V
Capacity	22 AH (c20)
CCR -18°C (EN)	300 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,32 +/- 0,01Kg/ I (25°)
Size (LxWxH)	115 x 100 x 214 mm
Weight	3,1 kg
Pos. of Terminal	1
Technology	Sealed maintenance-free AGM battery with heavily compressed plate packs electrolyte held in glass fibre separators
Terminal	I PRONT
Degassing	3







Landport Batteries Ramgatseweg 63 4941VN Raamsdonksveer