



intAct Bike-Power AGM HVT

Sealed maintenance-free AGM battery with heavily compressed plate packs | electrolyte absorbed in glass fibre separators | absolutely maintenance-free

Art.No.

IH HVT-10

Japancode

YB2-6, 66006-29F

Volt	6V
Capacity	22 Ah (c20)
CCR -18°C (EN)	300 A (EN)
Electrolyte	diluted sulphuric acid
Size (LxWxH)	115 x 100 x 214 mm
Weight	3,1 kg
Pos. of Terminal	1
Terminal	I
Base plate	-

Usage




Extremely vibration-resistant design

The durable energy bundle absorbs the strongest shocks from Harleys and other high-capacity bikes and also starts two-wheelers with high electrical energy requirements (e.g. with ABS). Our recommendation for motorcycles that need a lot of starting power and of course with strong vibrations.


- » Perfect for **Harleys** and other bikes with **high-capacity 2-cylinder engines**.
- » **Highest cold cranking amper:** For two-wheelers with high energy requirements, e.g. due to ABS safety technology.
- » **Extremely vibration-resistant.** Plate packs compressed and precisely fitted into the battery box.
- » **Robust housing made of impact-resistant plastic.** For heavy mechanical stress.
- » **Leak-proof. Can be installed at an angle,** as the electrolyte is absorbed in glass fibre mat.
- » **Sealed maintenance-free.**




Size



Pos. of Terminal 1



Terminal I



Base plate -