## **Motorcycle Batteries**



## intAct Bike-Power SLA

Sealed maintenance-free AGM battery (electrolyte held in Absorbent Glass Mat separators) | wet charged











## **READY-TO-USE ALL-ROUNDER**

Withstands the frequent charging cycles in seasonal use and on many short trips slightly better than conventional flooded batteries and starts reliably even when not fully charged. Our recommendation for an inexpensive absolutely maintenance-free battery.

- » High power reserve. Significant starting power even when partially discharged.
- **» Shake-proof.** The plates are firmly embedded in the glass fibre mat.
- » Sealed maintenance-free with gas recombination, where refilling is neither possible nor necessary.
- » Leak-proof. The battery can be installed at an angle, as the electrolyte is held in a glass fibre mat and the battery is factory sealed.
- » Wet charged. Ready to use.


## Datasheet





Artnum.	IS SLA 12-22
Japan-Code	52113
Volt	12V
Capacity	22 AH (c20)
CCR -18°C (EN)	230 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,32 +/- 0,01 kg/l (25°)
Size (LxWxH)	185 x 80 x 170 mm
Weight	6,2 kg
Pos. of Terminal	0
Technology	Sealed maintenance-free AGM battery (electrolyte held in Absorbent Glass Mat separators)   wet charged
Terminal	G FRONT







Base plate