



intAct **Bike-Power AGM SLA**

Sealed maintenance-free AGM battery (electrolyte absorbed in glass fibre mats) | wet charged



intAct **Bike-Power AGM SLA**

The powerful AGM motorcycle battery

Withstands the charging cycles of seasonal use and many short trips better than conventional wet batteries and starts reliably even when not fully charged.

Our recommendation if you are looking for an inexpensive, absolutely maintenance-free AGM motorcycle battery.

CHARACTERISTICS

- » **High power reserve.** Significant starting power even when partially discharged.
- » **Shake-proof.** The plates are firmly embedded in the glass fibre mat.
- » **Sealed maintenance-free** with gas recombination, where refilling is neither possible nor necessary.
- » **Leak-proof.** The battery can be installed at an angle, as the electrolyte is absorbed in a glass fibre mat and the battery is factory sealed.
- » Wet charged. **Ready to use.**

LANDPORT
BATTERIES

Ramgatsweg 63 // NL - 4941 VN Raamsdonksveer
Phone: +31 (0) 162 58 14 00 // Fax: +31 (0) 162 58 14 01
info@landportbv.com // www.landportbv.com

intAct
BATTERY - POWER

ALWAYS THE
BATTERY
THAT FITS!

intAct **Bike-Power AGM SLA**

Sealed maintenance-free AGM battery (electrolyte absorbed in glass fibre mats) | wet charged

Item Nr.	Volt	Capacity	Cold crank-ing amper	Length mm	Width mm	Height mm	Position of Terminal	Terminal	Base plate	Degas-sing	Weight/ kg
IS CT4B-5	12	2,3 Ah (c20)	50 A (EN)	113	39	86	Plug	K	-	-	0.95
IS CTZ5-S	12	4 Ah (c20)	50 A (EN)	113	69	85	0	A	-	-	1.43
IS CB5-3	12	5 Ah (c20)	70 A (EN)	120	60	128	0	B	-	-	1,8
IS CTX7A-BS	12	6 Ah (c20)	80 A (EN)	150	86	94	1	A	-	-	2.46
IS CTZ7-S	12	6 Ah (c20)	80 A (EN)	113	69	105	0	A	-	-	1.92
IS CT7B-4	12	6,5 Ah (c20)	80 A (EN)	150	65	92	1	A	-	-	2.49
IS CTZ7V	12	7,0 Ah (c20)		113	70	120			-	-	2.32
IS CTZ8V	12	7,0 Ah (c20)	120 A (EN)	113	70	130	0	A	-	-	2.56
IS CT9B-4	12	8 Ah (c20)	100 A (EN)	150	69	105	1	A	-	-	2.93
IS CTX9-BS	12	8 Ah (c20)	120 A (EN)	150	86	105	1	A	-	-	2.89
IS CTZ10-S	12	8,5 Ah (c20)	140 A (EN)	150	86	94	1	A	-	-	2.75
IS CT12-10Z	12	10 Ah (c20)		194	59	112			-	-	3.2
IS CT12B-4	12	10 Ah (c20)	150 A (EN)	150	69	130	1	A	-	-	3.57
IS CTZ12-S	12	11 Ah (c20)	190 A (EN)	150	86	110	1	A	-	-	3.35
IS CTZ14-S	12	11,5 Ah (c20)	200 A (EN)	150	86	110	1	A	-	-	3.35
IS CT14B-4	12	12 Ah (c20)	190 A (EN)	150	69	145	1	A	-	-	4.23
IS CTX14-BS	12	12 Ah (c20)	180 A (EN)	150	86	145	1	A	-	-	4.54
IS SLA 12-22	12	22 Ah (c20)	230 A (EN)	181	77	167	0	G	-	-	6
IS CTX30L-BS	12	30 Ah (c20)	360 A (EN)	167	127	176	0	A	-	-	9.42

