

Item Code: PRO 68034SHD
EAN: 8717101027189


Description

Dynac Professional SMF (Sealed Maintenance Free) is produced with an advanced labyrinth system for recombination of gases which reduces water loss. Its design provides enhanced safety due to integrated arrestors and excellent endurance and service life. Ideal for modern commercial and heavy-duty vehicles with high electrical equipment.


Specifications

Nominal Voltage	12	
Rated Capacity (25 °C)	180.00 Ah	20hr, 9.00A, 1.75V/cell
Cold Cranking Current (EN)	1000 A	
Technology	Flooded Calcium	
Separator	PE	
Container Material	Polypropylene	
Box Type	B	
Approx. Weight	43.60 Kg (76.28lbs)	
Layout	3	
Terminal	1	
Hold-down	-	
Dimensions	Length	513 mm
	Width	223 mm
	Height	203 mm
	Total Height	223 mm

Terminal



Position of terminal



Hold-down

-



Battery Classifications EN 50342-6

Water Consumption	Charge Retention	Vibrations Resistance	Endurance Level	Micro-Cycle Performance
W4	C2	V2	E2	-

Certificates / Standards

- CE Certified



(Note) All above information shall be changed without prior notice, Landport Batteries reserves the right to explain and update the latest information