

DYNAC PROFESSIONAL SHD

ACLPV SHD63013N EAN CODE: 8717101011904

Description

Professional SHD (Super Heavy duty) is produced with glass fiber separators which offers higher cycling ability. Its design provides enhanced vibration resistance and great endurance and service life. Recommended for commercial and heavy-duty vehicles with standard electrical equipment.

Performance	
Nominal Voltage	12
Capacity	130Ah (20hr, 1.75V/cell)
CCA EN	680

Dimensions / Casing / Weight

Technical Characteristics	
Technology	Flooded Calcium
Seperator	PE

Layout	Terminal
+ _	$ \begin{array}{c} \bullet & \emptyset & 19,5 \\ \hline \bullet & & & \bullet & \emptyset & 17,9 \\ \hline \bullet & & & & & \bullet & & & \\ \hline \bullet & & & & & & & \\ \hline \bullet & & & & & & & \\ \hline \bullet & & & & & & & \\ \hline \bullet & & & & & & & \\ \hline \bullet & & & & & & & \\ \hline \bullet & & & & & & \\ \hline \bullet & & & & & & \\ \hline \bullet & & & & & & \\ \hline \bullet & & & & & & \\ \hline \bullet & & & & & & \\ \hline \bullet & & & & & & \\ \hline \bullet & & & & & & \\ \hline \bullet & & & & & & \\ \hline \bullet & & & & & & \\ \hline \bullet & & & & & & \\ \hline \bullet & & & & & \\ \hline \bullet & & & & & & \\ \hline \bullet & & & & \\ \hline \bullet & & & & & \\ \hline \bullet & & & $

Battery Classifications	as per EN 50342-6			
Water Consumption	Charge Retention	Vibration Resistance	Endurance Level	Micro-Cycle Performance
W3	C2	V2	E2	
(Note) All above information shall be changed without prior notice, Landport Batteries reserves the right to explain and update the latest information.			the right	



Advanced starting power

cycling stability

equipment

life

Glass fiber separators > Higher

Enhanced vibration resistance Advanced endurance and service

Vehicles with standard electrical

Features

٠

•

•

07/06/2022