EAN CODE: 8717101017401

Description

Dynac Semi-Traction is a semi-traction battery which provides energy for onboard energy consumers of motorhomes, caravans and boats or trucks and buses. These onboard energy consumers, such as lighting, refrigerators and onboard computers or tail lifts, demand massive cyclic performance of a battery. Dynac Semi-Traction is resistant to deep discharges up to 50% and is suitable for seasonal use. Ideal for leisure vehicles with light to medium power consumers. Available in a range of 12V batteries from 50Ah to 230Ah in series wet charged and sealed maintenance free (SMF).

Performance		
Nominal Voltage	12	
Capacity	180Ah (20hr, 1.75V/cell)	
Capacity	135Ah (5hr, 1.7V/cell)	
RC 25A	365	

Dimensions / Casing / Weight				
Вох Туре	В			
Dimensions	Length: 513 mm Width: 223 mm Height: 203 mm Total Height: 223 mm			
Net Weight Acid Volume	47.5 Kg			
Material Casing / Lid	Polypropylene			

Technical Characteristics			
Technology	Flooded Low Antimony		
Seperator	DE		

Charging instructions	
Cycle use charge recommendation, Voltage	14.7
Cycle use charge recommendation, Max Amps	18
Float charge recommendation, Voltage	13.38
Float charge recommendation Max Amps	1.8
Cycles at 50% DoD	400



Features

- Reliable power supply
- Deep discharges up to 50%
- Ideal for seasonal use
- Available as wet charged or sealed maintenance free (SMF)
- Recommended for leisure vehicles with light to medium power consumers

Layout	Terminal
+	(Keggel 1,6 1

Battery Classifications as per EN 50342-6				
Water Consumption	Charge Retention	Vibration Resistance	Endurance Level	
W2	C2	V1	E2	

(Note) All above information shall be changed without prior notice, Landport Batteries reserves the right to explain and update the latest information.